


### Product type designation

Product description

### PROFIBUS FC Standard Cable GP

Standard bus cable (2-core), sold by the meter, unassembled PROFIBUS FC Standard Cable GP, bus cable 2-wire, shielded special configuration for quick assembly, Delivery unit: max. 1000 m, Minimum order 20 m Sold by the meter



Suitability for use

Standard cable specially designed for fast, permanent installation

Cable designation

02YSY (ST) CY 1x2x0,64/2,55-150 VI KF 40 FR

### Electrical data

Damping ratio per length

• at 9.6 kHz / maximum	0.0025 dB/m
• at 38.4 kHz / maximum	0.004 dB/m
• at 4 MHz / maximum	0.022 dB/m
• at 16 MHz / maximum	0.042 dB/m

Impedance

• Rated value	150 $\Omega$
• at 9.6 kHz	270 $\Omega$
• at 38.4 kHz	185 $\Omega$
• at 3 MHz ... 20 MHz	150 $\Omega$

Relative symmetrical tolerance

• of the characteristic impedance at 9.6 kHz	10 %
• of the characteristic impedance at 38.4 kHz	10 %

<ul style="list-style-type: none"> <li>• of the characteristic impedance at 3 MHz ... 20 MHz</li> </ul>	10 %
Loop resistance per length / maximum	110 mΩ/m
Shield resistance per length / maximum	9.5 Ω/km
Capacity per length / at 1 kHz	28.5 pF/m
Operating voltage	
<ul style="list-style-type: none"> <li>• RMS value</li> </ul>	100 V

### Mechanical data

Number of electrical cores	2
Design of the shield	Overlapped aluminum-clad foil, sheathed in a braided screen of tin-plated copper wires
Type of electrical connection / FastConnect	Yes
Outer diameter	
<ul style="list-style-type: none"> <li>• of inner conductor</li> </ul>	0.65 mm
<ul style="list-style-type: none"> <li>• of the wire insulation</li> </ul>	2.55 mm
<ul style="list-style-type: none"> <li>• of the inner sheath of the cable</li> </ul>	5.4 mm
<ul style="list-style-type: none"> <li>• of cable sheath</li> </ul>	8 mm
Symmetrical tolerance of the outer diameter / of cable sheath	0.4 mm
Material	
<ul style="list-style-type: none"> <li>• of the wire insulation</li> </ul>	polyethylene (PE)
<ul style="list-style-type: none"> <li>• of the inner sheath of the cable</li> </ul>	PVC
<ul style="list-style-type: none"> <li>• of cable sheath</li> </ul>	PVC
Color	
<ul style="list-style-type: none"> <li>• of the insulation of data wires</li> </ul>	red/green
<ul style="list-style-type: none"> <li>• of cable sheath</li> </ul>	Violet
Bending radius	
<ul style="list-style-type: none"> <li>• with single bend / minimum permissible</li> </ul>	37.5 mm
<ul style="list-style-type: none"> <li>• with multiple bends / minimum permissible</li> </ul>	75 mm
Tensile load / maximum	100 N
Weight per length	78 kg/km

### Permitted ambient conditions

Ambient temperature	
<ul style="list-style-type: none"> <li>• during operation</li> </ul>	-40 ... +75 °C
<ul style="list-style-type: none"> <li>• during storage</li> </ul>	-40 ... +75 °C
<ul style="list-style-type: none"> <li>• during transport</li> </ul>	-40 ... +75 °C
<ul style="list-style-type: none"> <li>• during installation</li> </ul>	-40 ... +75 °C
<ul style="list-style-type: none"> <li>• Note</li> </ul>	Electrical properties measured at 20 °C, tests according to DIN 47250 part 4 respectively DIN VDE 0472
Burning behavior	flame resistant according to IEC 60332-3-24 (Category C) and UL 1685 (CSA FT 4)

Class of burning behaviour / according to EN 13501-6	Eca
Chemical resistance <ul style="list-style-type: none"> <li>• to mineral oil</li> <li>• to grease</li> <li>• to water</li> </ul>	oil resistant according to IEC 60811-2-1 (4 h / 70°C) Conditional resistance conditional resistance
Radiological resistance / to UV radiation	resistant

### Product properties, functions, components / general

Product feature <ul style="list-style-type: none"> <li>• halogen-free</li> <li>• silicon-free</li> </ul>	No Yes
--	-----------

### Standards, specifications, approvals

UL/ETL listing / 300 V Rating	Yes
UL/ETL style / 600 V Rating	Yes
Certificate of suitability <ul style="list-style-type: none"> <li>• CE marking</li> <li>• UL approval</li> <li>• RoHS conformity</li> </ul>	Yes Yes Yes
Marine classification association <ul style="list-style-type: none"> <li>• American Bureau of Shipping Europe Ltd. (ABS)</li> <li>• Bureau Veritas (BV)</li> <li>• Det Norske Veritas (DNV)</li> <li>• Germanische Lloyd (GL)</li> <li>• Lloyds Register of Shipping (LRS)</li> <li>• Nippon Kaiji Kyokai (NK)</li> <li>• Polski Rejestr Statkow (PRS)</li> </ul>	No No No No No No No

### Further Information / Internet Links

Internet-Link <ul style="list-style-type: none"> <li>• to website: Selector SIMATIC NET SELECTION TOOL</li> <li>• to website: Industrial communication</li> <li>• to website: Industry Mall</li> <li>• to website: Information and Download Center</li> <li>• to website: Image database</li> <li>• to website: CAx Download Manager</li> <li>• to website: Industry Online Support</li> </ul>	<a href="http://www.siemens.com/snst">http://www.siemens.com/snst</a>  <a href="http://www.siemens.com/simatic-net">http://www.siemens.com/simatic-net</a> <a href="https://mall.industry.siemens.com">https://mall.industry.siemens.com</a> <a href="http://www.siemens.com/industry/infocenter">http://www.siemens.com/industry/infocenter</a> <a href="http://automation.siemens.com/bilddb">http://automation.siemens.com/bilddb</a> <a href="http://www.siemens.com/cax">http://www.siemens.com/cax</a> <a href="https://support.industry.siemens.com">https://support.industry.siemens.com</a>
--	---

**last modified:** 02/12/2019